

Description

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS9072639
Minimum Qty (MOQ):	45 EA
NSN:	5306-00-225-9094
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS90726-39 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.