

Description

Fastener Length: 3-3/4", Thread: 1/4-24, Thread Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | MS9072647 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-225-9102 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS90726-47 Specifications

| | |
|----------------------------------------------|---------------------------------------------------------------------|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum |
| Fastener Length: | 3.656 Inches Minimum And 3.750 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 6950 Pounds Per Square Inch |
| Hardness Rating: | 23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae Gr 5 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-47> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.