

**Description**

Fastener Length: 1-3/4", Thread: 3/8-24, Thread Length: 1-3/16", hex head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[B1821BH038F175N](#)

SKU / Model:	MS9072665
Minimum Qty (MOQ):	10
NSN:	5305-00-269-3241
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS90726-65 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.000 Inches Minimum And 1.188 Inches Maximum
<b>Fastener Length:</b>	1.688 Inches Minimum And 1.750 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.226 Inches Minimum And 0.243 Inches Maximum
<b>Width Between Flats:</b>	0.551 Inches Minimum And 0.562 Inches Maximum
<b>End Item Identification:</b>	Mrap-rg-33 Armored Utility Vehicle (auv)
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	150000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Sae Gr 8 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Zinc Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-65> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.