

Description

Fastener Length: 7/8", Thread: 7/16-20, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS9072684 |
| Minimum Qty (MOQ): | 50 EA |
| NSN: | 5305-00-709-8283 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS90726-84 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Maximum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.272 Inches Minimum And 0.291 Inches Maximum |
| Width Between Flats: | 0.612 Inches Minimum And 0.625 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sae J429 Grade 8 Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 8 Grade |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-84> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.