



Military-Fasteners.com

P/N MS90726-9

## Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 15/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS907269                                  |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-068-0516                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS90726-9 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 2a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.750 Inches Minimum And 0.938 Inches Maximum                         |
| <b>Fastener Length:</b>                               | 1.125 Inches Nominal  |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.150 Inches Minimum And 0.163 Inches Maximum                         |
| <b>Width Between Flats:</b>                           | 0.428 Inches Minimum And 0.438 Inches Maximum                         |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Minimum Tensile Strength:</b>                      | 150000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall   |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum Overall           |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Material Document And Classification:</b>          | Sae J429 Gr8 Assn Std Single Material Response Overall                |
| <b>Surface Treatment:</b>                             | Zinc Overall And Chromate Overall                                     |
| <b>Surface Treatment:</b>                             | Zinc And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall        |
| <b>Thread Series Designator:</b>                      | Unf   |
| <b>Specification/standard Data:</b>                   | 05047-aes01f250a12aw9a91 Professional/industrial Association Standard |
| <b>Nondefinitive Spec/std Data:</b>                   | 2 Type And 10p Style And 8 Grade                                      |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.