

Description

Fastener Length: 1-63/64", Thread: 7/16-20, Thread Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072691
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-709-8542
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS90726-91 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Minimum And 1.313 Inches Maximum
Fastener Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.272 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae J429 Gr8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style And 8 Grade

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS90726-91> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.