

P/N MS90727-33

Military-Fasteners.com

Description

Fastener Length: 27/32", Thread: 5/16-24, Thread Length: 7/8",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS9072733
Minimum Qty (MOQ):	25
NSN:	5305-00-051-4075
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS90727-33 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	4.890 Inches Minimum And 5.000 Inches Maximum
End Item Identification:	W/s:radar Set, Firefinder (an/tpq-36); Filter Unit, Gas Particulate, M56; Spruance Class Dd (963); Central Office, Telephone Auto; Armored Vehicle Launch Bridge (m60a1 & M45a5); Tactical Air Opns Module (an/tyq-23); Collective Protective Equipment Cbr, M10; Ticonderoga Class Cg (47); Field Artillery Ammunition Support Vehicle (faagv)(m992)
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	8700 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sae J429 Gr8 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	2 Type And 10p Style And 8 Grade

How to Order

Order this hexagon head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90727-33</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.