

Description

Fastener Length: 3-5/32", Thread: 1/2-13, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS90728120 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-071-2076 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS90728-120 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.250 Inches Minimum And 1.442 Inches Maximum |
| Fastener Length: | 3.156 Inches Minimum And 3.250 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.302 Inches Minimum And 0.323 Inches Maximum |
| Width Between Flats: | 0.736 Inches Minimum And 0.750 Inches Maximum |
| End Item Identification: | Mrap Rg-33 Auv |
| Nominal Thread Diameter: | 0.500 Inches |
| Thread Quantity Per Inch: | 13 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum Overall |
| Surface Finish: | 63.0 Microinches Threads |
| Material: | Steel Overall |
| Material Document And Classification: | Saej429 Grade 8 Assn Std Single Material Response Or Astma354 Grade Bd Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90728-120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.