

## P/N MS90728-120

### **Description**

Fastener Length: 3-5/32", Thread: 1/2-13, Thread Length: 1-1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS90728120

Minimum Qty (MOQ): 25

NSN: 5305-00-071-2076

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS90728-120 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum And 1.442 Inches Maximum
Fastener Length:	3.156 Inches Minimum And 3.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
End Item Identification:	Mrap Rg-33 Auv
Nominal Thread Diameter:	0.500 Inches
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Saej429 Grade 8 Assn Std Single Material Response Or Astma354 Grade Bd Assn Std Single Material Response Overall
Surface Treatment:	Zinc And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this hexagon head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90728-120">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90728-120</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.