



Military-Fasteners.com

P/N MS90728-38

Description

Fastener Length: 1-7/16", Thread: 5/16-18, Thread Length: 0-7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9072838
Minimum Qty (MOQ):	1
NSN:	5305-00-226-4831
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS90728-38 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	1.438 Inches Minimum And 1.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
End Item Identification:	Mrap Buffalo Mk2a2
End Item Identification:	Mrap Buffalo Mk2a2; Mrap - Cougar Cat1 A2; Medium Mine Protected Vehicle - Mmpv
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum And 38.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Sae J429 Grade 8 Assn Std Single Material Response Or Astm A354 Grade Bd Assn Std Single Material Response Overall
Surface Treatment:	Zinc And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style And 8 Grade

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90728-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.