



Military-Fasteners.com

P/N MS90728-46

Description

Fastener Length: 3-13/32", Thread: 5/16-18, Thread Length: 0-7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS9072846 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5306-00-226-4839 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS90728-46 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum And 1.062 Inches Maximum |
| Fastener Length: | 3.406 Inches Minimum And 3.500 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.195 Inches Minimum And 0.211 Inches Maximum |
| Width Between Flats: | 0.489 Inches Minimum And 0.500 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Surface Finish: | 63.0 Microinches Threads |
| Material: | Steel Overall |
| Material Document And Classification: | Sae J429 Grade 8 Assn Std Single Material Response Overall Or Astm A354 Grade Bd Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Sc 3 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS90728-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.