

Description

Fastener Length: 1/2", Hole Diameter: ", Thread: 1/4-28, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS908906
Minimum Qty (MOQ):	20
NSN:	5306-00-825-4803
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9089-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum
Fastener Length:	0.500 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.070 Inches Nominal
Hole Diameter:	0.062 Inches Nominal
First Diameter From Head:	0.221 Inches Minimum And 0.231 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9089-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.