

**Description**

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS911111                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-322-7318                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS9111-11 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.626 Inches Nominal                               |
| <b>Fastener Length:</b>                      | 1.188 Inches Nominal                               |
| <b>Head Style:</b>                           | Double Hexagon W/hole                              |
| <b>Head Height:</b>                          | 0.330 Inches Nominal                               |
| <b>Width Between Flats:</b>                  | 0.305 Inches Minimum And 0.313 Inches Maximum      |
| <b>Extended Washer Diameter:</b>             | 0.438 Inches Nominal                               |
| <b>Extended Washer Thickness:</b>            | 0.050 Inches Minimum And 0.060 Inches Maximum      |
| <b>Grip Diameter:</b>                        | 0.2494 Inches Minimum And 0.2499 Inches Maximum    |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches                                       |
| <b>Grip Length:</b>                          | 0.562 Inches Nominal                               |
| <b>Thread Quantity Per Inch:</b>             | 28   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head           |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                              |
| <b>Material:</b>                             | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b> | Ams 5731 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9111-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.