

**Description**

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS911114
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-123-8515
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9111-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Maximum
<b>Fastener Length:</b>	1.375 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.330 Inches Nominal
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.313 Inches Maximum
<b>Extended Washer Diameter:</b>	0.438 Inches Nominal
<b>Extended Washer Thickness:</b>	0.060 Inches Minimum And 0.070 Inches Maximum
<b>Grip Diameter:</b>	0.2494 Inches Minimum And 0.2499 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.750 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9111-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.