

Description

Fastener Length: 1-7/16", Thread: 1/4-28, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS911115
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-123-8517
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9111-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.626 Inches Maximum
Fastener Length:	1.438 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Grip Diameter:	0.2494 Inches Minimum And 0.2499 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.812 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9111-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.