

Description

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS911117
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-216-5691
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9111-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.533 Inches Minimum And 0.634 Inches Maximum
Fastener Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.320 Inches Minimum And 0.340 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Grip Diameter:	0.2494 Inches Minimum And 0.2499 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.868 Inches Minimum And 0.898 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Undercut 0.221 Inch Min,0.231 Inch Max Dia.; 0.050 Inch Min,0.060 Inch Max Length
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9111-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.