

## P/N MS9112-07

### **Description**

Fastener Length: 1-1/32", Thread: 5/16-24, Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS911207
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-386-9014
Schedule B:	7318.15.8085
FCCN:	FΔRQQ



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9112-07 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.626 Inches Nominal
Fastener Length:	1.031 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3119 Inches Minimum And 0.3124 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.312 Inches Nominal
Thread Quantity Per Inch:	24
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9112-07">https://military-fasteners.com/bolts/machine+bolts/MS9112-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.