

Description

Fastener Length: 1-1/32", Thread: 5/16-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS911207 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-386-9014 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N MS9112-07 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.626 Inches Nominal |
| Fastener Length: | 1.031 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.375 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.500 Inches Nominal |
| Extended Washer Thickness: | 0.050 Inches Minimum And 0.060 Inches Maximum |
| Grip Diameter: | 0.3119 Inches Minimum And 0.3124 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.312 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Material: | Iron Alloy 660 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9112-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.