

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS912202
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-298-2763
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9122-02 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.386 Inches Minimum And 0.448 Inches Maximum
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Hexagon
Head Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8740
Screw Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9122-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.