

**Description**

Fastener Length: 1-7/16", Thread: 10-32, Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS914621                                  |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5306-00-753-7027                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS9146-21 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.626 Inches Minimum   |
| <b>Fastener Length:</b>                               | 1.438 Inches Nominal   |
| <b>Head Style:</b>                                    | Double Hexagon W/hole  |
| <b>Head Height:</b>                                   | 0.260 Inches Nominal   |
| <b>Width Between Flats:</b>                           | 0.243 Inches Minimum And 0.251 Inches Maximum  |
| <b>Extended Washer Diameter:</b>                      | 0.375 Inches Nominal   |
| <b>Extended Washer Thickness:</b>                     | 0.040 Inches Minimum And 0.050 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.812 Inches Nominal   |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall                            |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 63.0 Microinches Grip  |
| <b>Material:</b>                                      | Steel Comp 8740 Overall Or Steel Comp 8640 Overall   |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9146-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.