

P/N MS9147-15

Description

Fastener Length: 1-1/16", Thread: 1/4-28, Thread Length: 17/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS914715
Minimum Qty (MOQ):	5
NSN:	5306-01-499-0003
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9147-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.252 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	1.062 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
End Item Identification:	C5 Acft
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Material:	Steel Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9147-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9147-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9147-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9147-15 and selecting the quantity you want https://military-fasteners.com/bolts/machine+bolts/ms9147-15 and selecting the quantity you want https://military-fasteners.com/bolts/ms9147-15 and selecting the quantity you want https://military-fasteners.com/bolts/ms9147-15 and selecting the quantity you want https://military-fasteners.com/bolts/ms9147-15 and selecting the property of th