



Military-Fasteners.com

P/N MS9147-19

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS914719
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-295-5201
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9147-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	1.312 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
First Diameter From Head:	0.221 Inches Minimum And 0.231 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.502 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Externally Relieved Body Diameter Quantity:	1
Special Features:	Surface Finishon Threads 32 Microinches; Grip And Bearing Surface Of Head 63 Microinches
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9147-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.