

Description

Fastener Length: 13/16", Thread: 5/16-24, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS914809
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-827-7619
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9148-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Minimum
Fastener Length:	0.812 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9148-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.