

**Description**

Fastener Length: 11/16", Thread: 8-36, Thread Length: 39/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS920709
Minimum Qty (MOQ):	10
NSN:	5305-01-261-1868
Schedule B:	7318.15.6080
ECCN:	EAR99



## P/N MS9207-09 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.606 Inches Minimum And 0.626 Inches Maximum
<b>Fastener Length:</b>	0.688 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/ Hole
<b>Head Height:</b>	0.250 Inches Nominal
<b>Width Between Flats:</b>	0.212 Inches Minimum And 0.220 Inches Maximum
<b>Extended Washer Diameter:</b>	0.312 Inches Nominal
<b>Extended Washer Thickness:</b>	0.030 Inches Minimum And 0.040 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Hardness Rating:</b>	42.0 Rockwell C Minimum And 46.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 601
<b>Screw Material Document And Classification:</b>	Ams 6304 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Nickel And Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std All Treatment Responses
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9207-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.