

P/N MS9207-09

Description

Fastener Length: 11/16", Thread: 8-36, Thread Length: 39/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS920709

Minimum Qty (MOQ):

NSN: 5305-01-261-1868

Schedule B: 7318.15.6080

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N MS9207-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.606 Inches Minimum And 0.626 Inches Maximum
Fastener Length:	0.688 Inches Nominal
Head Style:	Double Hexagon W/ Hole
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Extended Washer Diameter:	0.312 Inches Nominal
Extended Washer Thickness:	0.030 Inches Minimum And 0.040 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Hardness Rating:	42.0 Rockwell C Minimum And 46.0 Rockwell C Maximum
Screw Material:	Steel Comp 601
Screw Material Document And Classification:	Ams 6304 Assn Std Single Material Response
Screw Surface Treatment:	Nickel And Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS9207-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS9207-09 and selecting the quantity you