

**Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 43/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS920810
Minimum Qty (MOQ):	10
NSN:	5306-00-143-2013
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9208-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.658 Inches Minimum And 0.678 Inches Maximum
<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.260 Inches Nominal
<b>Width Between Flats:</b>	0.243 Inches Minimum And 0.251 Inches Maximum
<b>Extended Washer Diameter:</b>	0.375 Inches Nominal
<b>Extended Washer Thickness:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.072 Inches Minimum And 0.092 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp 601 Overall
<b>Material Document And Classification:</b>	Ams 6304 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9208-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.