

Description

Fastener Length: 15/16", Thread: 10-32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS920813 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-380-5590 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N MS9208-13 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.938 Inches Nominal |
| Head Height: | 0.260 Inches Nominal |
| Width Between Flats: | 0.243 Inches Minimum And 0.251 Inches Maximum |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.248 Inches Minimum And 0.308 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Nickel Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9208-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.