

## P/N MS9208-13

## **Description**

Fastener Length: 15/16", Thread: 10-32

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS920813

Minimum Qty (MOQ):

NSN: 5306-01-380-5590

Schedule B: 7318.15.8085

ECCN: EAR99









# P/N MS9208-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.938 Inches Nominal
Head Height:	0.260 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.248 Inches Minimum And 0.308 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Nickel Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9208-13">https://military-fasteners.com/bolts/machine+bolts/MS9208-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9208-13">https://military-fasteners.com/bolts/machine+bolts/MS9208-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9208-13">https://military-fasteners.com/bolts/machine+bolts/MS9208-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9208-13">https://military-fasteners.com/bolts/machine+bolts/MS9208-13</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/machine+bolts/ms9208-13">https://military-fasteners.com/bolts/ms9208-13</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms9208-13">https://military-fasteners.com/bolts/ms9208-13</a> and selecting the property of the property of