

P/N MS9208-16

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 41/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS920816

Minimum Qty (MOQ): 5

NSN: 5306-01-278-6622

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS9208-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.630 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
First Diameter From Head:	0.165 Inches Minimum And 0.175 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.435 Inches Minimum And 0.495 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams6304 Uns K14675 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Nickel Overall
Surface Treatment Document And Classification:	Ams2416 Assn Std All Treatment Responses Overall
Supplementary Features:	Acft Eng And Prop. Appl
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms9208 Government Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9208-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.