

**Description**

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 25/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS920923
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-390-1864
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N MS9209-23 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.780 Inches Nominal
<b>Fastener Length:</b>	1.562 Inches Nominal
<b>Head Style:</b>	Double Hexagon Extended Washer
<b>Head Height:</b>	0.330 Inches Nominal
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.313 Inches Maximum
<b>Extended Washer Diameter:</b>	0.438 Inches Nominal
<b>Extended Washer Thickness:</b>	0.060 Inches Minimum And 0.070 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 601 Overall
<b>Material Document And Classification:</b>	Ams6304 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams2416 Assn Std All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9209-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.