

Description

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS920930 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-532-4268 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N MS9209-30 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum And 0.810 Inches Maximum |
| Fastener Length: | 2.250 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.330 Inches Nominal |
| Width Between Flats: | 0.305 Inches Minimum And 0.313 Inches Maximum |
| Extended Washer Diameter: | 0.438 Inches Nominal |
| Extended Washer Thickness: | 0.060 Inches Minimum And 0.070 Inches Maximum |
| Grip Diameter: | 0.222 Inches Minimum And 0.232 Inches Maximum |
| End Item Identification: | Airborne Radar Astor |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Material: | Steel Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9209-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.