

## Description

Fastener Length: 1-1/8", Thread: 5/16-24, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS921014                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-143-3354                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS9210-14 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.875 Inches Minimum And 0.935 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 1.125 Inches Nominal  |
| <b>Head Style:</b>                                    | Double Hexagon W/hole   |
| <b>Head Height:</b>                                   | 0.375 Inches Nominal  |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>                      | 0.500 Inches Nominal  |
| <b>Extended Washer Thickness:</b>                     | 0.070 Inches Minimum And 0.080 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Grip Length:</b>                                   | 0.190 Inches Minimum And 0.250 Inches Maximum                       |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Hardness Rating:</b>                               | 42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall |
| <b>Hardness Rating:</b>                               | 42.0 Rockwell C Minimum And 46.0 Rockwell C Maximum Overall         |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Comp 601 Overall  |
| <b>Material Document And Classification:</b>          | Ams 6304 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Nickel Overall And Cadmium Overall                                  |
| <b>Surface Treatment:</b>                             | Nickel And Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams 2416 Assn Std All Treatment Responses Overall                   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9210-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.