

**Description**

Fastener Length: 3-1/64", Thread: 5/16-24, Thread Length: 29/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS921034
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-386-0973
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9210-34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.905 Inches Nominal
<b>Fastener Length:</b>	3.000 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.375 Inches Nominal
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Extended Washer Diameter:</b>	0.500 Inches Nominal
<b>Extended Washer Thickness:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	2.065 Inches Minimum And 2.125 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Hardness Rating:</b>	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 601 Overall
<b>Material Document And Classification:</b>	Ams 6304 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9210-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.