



Military-Fasteners.com

P/N MS9210-34

Description

Fastener Length: 3-1/64", Thread: 5/16-24, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS921034
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-386-0973
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9210-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.905 Inches Nominal
Fastener Length:	3.000 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.065 Inches Minimum And 2.125 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9210-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.