

Description

Fastener Length: 1-1/8", Thread: 3/8-24, Thread Length: 63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS921112
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-416-3033
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9211-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.990 Inches Nominal
Fastener Length:	1.125 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.422 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.562 Inches Nominal
Extended Washer Thickness:	0.090 Inches Minimum And 0.100 Inches Maximum
First Diameter From Head:	0.343 Inches Minimum And 0.353 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.125 Inches Minimum And 0.145 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9211-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.