

P/N MS9217-09

Military-Fasteners.com

Description

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS921709
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-009-6636
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9217-09 Specifications

Head Length:0.586 Inches Minimum And 0.626 Inches Maximumiastener Length:0.678 Inches Minimum And 0.698 Inches Maximumlead Style:Double Hexagon Wholelead Height:0.260 Inches NominalWitch Between Flats:0.243 Inches Minimum And 0.251 Inches Maximumwitch Between Flats:0.243 Inches Minimum And 0.50 Inches Maximumwitch Between Flats:0.441 Inches Minimum And 0.050 Inches Maximumwitch Between Flats:0.441 Inches Minimum And 0.050 Inches Maximumwitch Between Flats:0.404 Inches Minimum And 0.050 Inches Maximumwitch Between Flats:0.404 Inches Minimum And 0.092 Inches Maximumlobel Diameter:0.044 Inches Nominallobel Auster Thickness:0.190 Inches Nominallobel Quantity:0.190 Inches Maximum And 0.092 Inches Maximumlobel Quantity:1910 Inches Minimum And 0.092 Inches Maximumlobel Quantity:1910 Inches Minimum And 0.092 Inches Maximumlobel Quantity:1910 Inches Maximum And 0.092 Inches Maximumlobel Gonfiguration Style:0010 Inches Searing Surface Oncell Add 6.0 Rockwell C Maximum Overalllobel Configuration Style:0010 Inches Bearing Surface Of Headlobel Configuration Style:32.0 Microinches Bearing Surface Of Headlobel Configuration Style:32.0 Microinches Threads </th <th>Thread Class:</th> <th>3a</th>	Thread Class:	3a
atener Length:0.678 Inches Minimu And 0.698 Inches Maximumtead Style:Double Hexagon W/holetead Height:O.600 Inches MominalVidth Between Flats:0.260 Inches Mominalkitended Washer Diameter:0.375 Inches Mominaltote Diameter:0.404 Inches Minimum And 0.050 Inches Maximumtote Diameter:0.404 Inches Minimum And 0.050 Inches Maximumtote Diameter:0.404 Inches Minimum And 0.050 Inches Maximumtote Diameter:0.404 Inches Minimum And 0.092 Inches Maximumtote Diameter:0.407 Inches Nominaltote Diameter:0.407 Inches Minimum And 0.092 Inches Maximumtote Diameter:0.407 Inches Minimum And 0.092 Inches Maximumtote Diameter:0.407 Inches Minimum And 0.092 Inches Maximumtote Quantity:4tote Diameter:Pilledtote Strength:95000 Ponds Per Square Inchtardness Rating:0.400 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overalltote Congueto Style:95000 Ponds Per Square Inchtardace Finish:32.0 Microinches Bearing Surface Of Headtardace Finish:32.0 Microinches Griptardace Finish:32.0 Micro	Thread Direction:	Right-hand
tead Style:Double Hexagon W/holetead Height:0.260 Inches NominalVidth Between Flats:0.243 Inches Minimum And 0.251 Inches Maximumtead Washer Diameter:0.375 Inches Nominaltextended Washer Thickness:0.404 Inches Minimum And 0.050 Inches Maximumtole Diameter:0.047 Inches Nominaltole Diameter:0.047 Inches Nominaltole Diameter:0.047 Inches Nominaltole Quantity:4tole Quantity:0.072 Inches Minimum And 0.092 Inches Maximumtole Quantity:0.071 Inches Minimum And 0.092 Inches Maximumtole Quantity:0.072 Inches Minimum And 0.092 Inches Maximumtole Conjection:0.072 Inches Minimum And 0.092 Inches Maximumtole Quantity:0.072 Inches Minimum And 0.092 Inches Maximumtole Quantity:1tole Conjection:0.072 Inches Maximum And 0.092 Inches Maximumtole Conjection:1000 Pounds Persquere Inchtole Conjection:1000 Pounds Persquere Inchtole Conjection:2000 Pounds Persquere Inchtole Conjection:32.0 Microinches Baring Surface Of Headtortace Finish:32.0 Microinches Griptortace Finish:32.0 Microinches Threadstortace Finish:32.0 Microinches Threadstortace Finish:36.04 Assn Std	Thread Length:	0.586 Inches Minimum And 0.626 Inches Maximum
tead Height:0.260 Inches NominalVidth Between Flats:0.243 Inches NominalVidth Between Flats:0.375 Inches NominalExtended Washer Diameter:0.040 Inches NominalIole Diameter:0.040 Inches NominalIominal Thread Diameter:0.904 Inches NominalIominal Thread Diameter:0.904 Inches NominalIole Quantity:0.972 Inches Minimum And 0.092 Inches MaximumIole Quantity:0.972 Inches Minimum And 0.092 Inches MaximumIole Type:0.972 Inches Minimum And 0.092 Inches MaximumIole Type:DilledIole Type:190 OnchesIole Type:190 OnchesIole Type:190 OnchesIole Configuration Style:2.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallIole Configuration Style:2.0 Nicroinches Bearing Surface Of HeadIoure Finish:3.2.0 Microinches GripIoure Finish:3.2.0 Microinches GripIourace Finish:3.2.0 Microinches ThreadsIourace Finish:Micel OverallIourace Finish:Micel OverallIourace Finish:Micel OverallIourace Finish:Micel Overall And Classification:Iourace Finish:Micel Overall And Classification:Iourace Finish:Micel Overall And Classification: <td< th=""><th>Fastener Length:</th><th>0.678 Inches Minimum And 0.698 Inches Maximum</th></td<>	Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Width Between Flats:0.243 Inches Minimum And 0.251 Inches MaximumExtended Washer Diameter:0.375 Inches NominalExtended Washer Thickness:0.040 Inches Minimum And 0.050 Inches MaximumIole Diameter:0.047 Inches MominalIominal Thread Diameter:0.190 InchesIole Quantity:0.72 Inches Minimum And 0.092 Inches MaximumIole Quantity:4Iole Type:DrilledIole Type:DrilledIole Type:DrilledIole Type:DrilledIole Configuration Style:195000 Pounds Per Square InchIardness Rating:4.2.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallIole Configuration Style:Double Hexagon Longitudinal HoleIordace Finish:32.0 Microinches Braing Surface Of HeadIordace Finish:32.0 Microinches GripIordace Finish:32.0 Microinches Maximum OverallIordace Finish:32.0 Microinches GripIordace Finish:32.0 Microinches GripIordace Finish:32.0 Microinches GripIordace Finish:32.0 Microinches ThreadsIordace Finish:32.0 Microinches ThreadsIordace Finish:32.0 Microinches ThreadsIordace Finish: <th>Head Style:</th> <th>Double Hexagon W/hole</th>	Head Style:	Double Hexagon W/hole
Extended Washer Diameter:0.375 Inches Nominalixtended Washer Thickness:0.040 Inches Minimum And 0.050 Inches Maximumitole Diameter:0.047 Inches Nominalitole Diameter:0.190 Inchesitrip Length:0.072 Inches Minimum And 0.092 Inches Maximumitole Quantity:4itole Quantity:0.072 Inches Minimum And 0.092 Inches Maximumitole Type:0.072 Inches Minimum And 0.092 Inches Maximumitole Type:0.072 Inches Minimum And 0.092 Inches Maximumitole Type:0.072 Inches Maximum And 0.092 Inches Anting:itole Configuration Style:0.920 Norounds Per Square Inchiturface Finish:92.00 Norounds Per Square Inchiturface Finish:92.00 Noroinches Bearing Surface Of Headiturface Finish:92.00 Microinches Gring Surface Of Headiturface Treatment:Mics Gold Assi Std Single Material Response Overalliturface Treatment:Nickel Overall And Cadmium Overalliturface Treatment Doc	Head Height:	0.260 Inches Nominal
Acte and Washer Thickness:0.040 Inches Minimum And 0.050 Inches MaximumIole Diameter:0.047 Inches NominalIominal Thread Diameter:0.190 InchesIole Quantity:0.072 Inches Minimum And 0.092 Inches MaximumIole Quantity:4Iole Type:DrilledIole Type:DrilledIonimal Thread Diameter:92Ionimal Thread Diameter:92Iole Type:DrilledIole Type:92Iole Type:92Iole Type:92Ionimal Thread Diameter:92Ionimal Thread Diameter:92	Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Inde Diameter: 0.047 Inches Nominal Indeminal Thread Diameter: 0.190 Inches Inde Guantity: 0.072 Inches Minimum And 0.092 Inches Maximum Inde Quantity: 4 Inde Type: Diriled Inde Aguantity Per Inch: 32 Inder Strength: 19500 Pounds Per Square Inch Inde Configuration Style: 0.000 Pounds Per Square Inch Inde Erinish: 32.000 Pounds Per Square Inch Inder Erinish: <td< th=""><th>Extended Washer Diameter:</th><th>0.375 Inches Nominal</th></td<>	Extended Washer Diameter:	0.375 Inches Nominal
Join Index0.190 InchesSirp Length:0.072 Inches Minimum And 0.092 Inches MaximumJole Quantity:4Jole Quantity:DiriledJoin Provided:Finished HeadFread Quantity Per Inch:9Join Pounds Per Square Inch9500 Pounds Per Square InchInimum Tensile Strength:9500 Pounds Per Square InchJoin Pounds Per Square Inch9000 Pounds Per Square InchJoi	Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Srip Length:0.072 Inches Minimum And 0.092 Inches MaximumIole Quantity:4Iole Quantity:DrilledIole Type:DrilledInterad Quantity Per Inch:32Inimum Tensile Strength:19500 Pounds Per Square InchInterder Strength:Double Per Square InchIole Configuration Style:Double Hexagon Longitudinal HoleIorace Finish:32.0 Microinches Bearing Surface Of HeadInterder Finish:Stol Microinches GripInterder Finish:Stol Microinches Microinches OverallInterder Finish:Stol Microinches ThreadsInterder Finish:Stol OverallInterder Finish:Microinches String Material Response OverallInterder Finish:Nickel Overall And Cadmium OverallInterder Finish:Microinches String Material Response OverallInterder Finish:Microinches Microinches Microinch	Hole Diameter:	0.047 Inches Nominal
No4Hole Quantity:DrilledHole Type:DrilledHeadures Provided:Finished HeadStread Quantity Per Inch:32Minimum Tensile Strength:195000 Pounds Per Square InchHardness Rating:42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleHardnese Finish:32.0 Microinches Bearing Surface Of HeadHardnese Finish:32.0 Microinches GripHardnese Finish:32.0 Microinches ThreadsHardrafer Finish:32.0 Microinches ThreadsHardrafer Finish:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Slingle Material Response OverallHardrafer Treatment:Nickel Overall And Cadmium Overall	Nominal Thread Diameter:	0.190 Inches
Nole Type:Drilleddeatures Provided:Finished Head'hread Quantity Per Inch:32Ainimum Tensile Strength:195000 Pounds Per Square InchBardness Rating:42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallNole Configuration Style:Double Hexagon Longitudinal HoleBardness Finish:32.0 Microinches Bearing Surface Of HeadBardnese Finish:32.0 Microinches GripBardnese Finish:32.0 Microinches GripBardnese Finish:32.0 Microinches GripBardnese Finish:32.0 Microinches Style:Bardnese Finish:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallBardnese Treatment:Nickel Overall And Cadmium OverallBardnese Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Provided:Finished HeadPhread Quantity Per Inch:32Minimum Tensile Strength:195000 Pounds Per Square InchMardness Rating:42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleHole Configuration Style:32.0 Microinches Bearing Surface Of HeadHardness Rating:32.0 Microinches GripHardness Rating:32.0 Microinches GripHardness Rating:32.0 Microinches GripHardness Rating:32.0 Microinches ThreadsHardness Rating:Steel Comp 601 OverallMaterial Document And Classification:Nickel Overall And Cadmium OverallHardness Rating:Nickel Overall And Cadmium OverallHardness Rating:Nickel Overall And Cadmium Overall	Hole Quantity:	4
Arread Quantity Per Inch: 32 Minimum Tensile Strength: 195000 Pounds Per Square Inch Marchess Rating: 42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall Nole Configuration Style: Double Hexagon Longitudinal Hole Sturface Finish: 32.0 Microinches Bearing Surface Of Head Sturface Finish: 32.0 Microinches Grip Sturface Finish: 32.0 Microinches Grip Sturface Finish: 32.0 Microinches Threads Material Document And Classification: Ams 6304 Assn Std Single Material Response Overall Sturface Treatment: Nickel Overall And Cadmium Overall Sturface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Hole Type:	Drilled
Ainimum Tensile Strength:195000 Pounds Per Square InchHardness Rating:42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleHord Configuration Style:Double Hexagon Longitudinal HoleSturface Finish:32.0 Microinches Bearing Surface Of HeadSturface Finish:32.0 Microinches GripSturface Finish:32.0 Microinches GripAterial:Steel Comp 601 OverallAterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSturface Treatment:Nickel Overall And Cadmium OverallSturface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Features Provided:	Finished Head
Hardness Rating:42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Mas 2416 Assn Std All Treatment Responses Overall	Thread Quantity Per Inch:	32
Note Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ans 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ans 2416 Assn Std All Treatment Responses Overall	Minimum Tensile Strength:	195000 Pounds Per Square Inch
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripAterial:32.0 Microinches ThreadsMaterial:Steel Comp 601 OverallMaterial Document And Classification:Microinches Strigle Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment And Classification:Microinches Strigle Material Response Overall	Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsAterial:Steel Comp 601 OverallAterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Steel Comp 601 Overall Material Document And Classification: Ams 6304 Assn Std Single Material Response Overall Surface Treatment: Nickel Overall And Cadmium Overall Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Ams 6304 Assn Std Single Material Response Overall Surface Treatment: Nickel Overall And Cadmium Overall Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Surface Finish:	32.0 Microinches Threads
Surface Treatment: Nickel Overall And Cadmium Overall Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Material:	Steel Comp 601 Overall
Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
	Surface Treatment:	Nickel Overall And Cadmium Overall
bread Series Designator	Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses Overall
	Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9217-09</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.