

P/N MS9218-05

Description

Fastener Length: 17/32", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS921805
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-387-0521
Schedule B:	7318.15.8085
ECCN:	9A991



^{*} See page 2 for technical characteristics

P/N MS9218-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.349 Inches Nominal
Fastener Length:	0.527 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.222 Inches Minimum And 0.232 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.079 Inches Minimum And 0.099 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9218-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.