

P/N MS9218-20

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 13/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS921820
Minimum Qty (MOQ):	5
NSN:	5306-01-236-7083
Schedule B:	7318.15.8085
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N MS9218-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.740 Inches Minimum And 0.820 Inches Maximum
Fastener Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.320 Inches Minimum And 0.340 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.565 Inches Minimum And 0.625 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9218-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.