

P/N MS9218-26

Description

Fastener Length: 1-3/4", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

| SKU / Model: | MS921826 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-320-5277 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9218-26 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.740 Inches Minimum And 0.820 Inches Maximum |
| Fastener Length: | 1.740 Inches Minimum And 1.760 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.320 Inches Minimum And 0.340 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.313 Inches Maximum |
| Extended Washer Diameter: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Extended Washer Thickness: | 0.060 Inches Minimum And 0.070 Inches Maximum |
| Hole Diameter: | 0.060 Inches Minimum And 0.070 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 195000 Pounds Per Square Inch |
| Hardness Rating: | 42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Double Hexagon Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp 601 Overall |
| Material Document And Classification: | Ams 6304 Assn Std Single Material Response Overall |
| Surface Treatment: | Nickel Overall And Cadmium Overall |
| Surface Treatment Document And Classification: | Ams 2416 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9218-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.