

Description

Fastener Length: 11/16", Thread: 1/4-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS921907 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5306-01-470-9787 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N MS9219-07 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.580 Inches Minimum And 0.600 Inches Maximum |
| Fastener Length: | 0.688 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.375 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.500 Inches Nominal |
| Extended Washer Thickness: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 601 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9219-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.