

## P/N MS9219-18

### **Description**

Fastener Length: 1-3/8", Hole Diameter: 3/32", Thread: 1/4-24, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS921918
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-398-1750
Schedule B:	7318.15.8085
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9219-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 0.935 Inches Maximum
Fastener Length:	1.375 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
Hole Diameter:	0.100 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.440 Inches Minimum And 0.500 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9219-18">https://military-fasteners.com/bolts/machine+bolts/MS9219-18</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.