

Description


Hole Diameter: 1/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS927608
Minimum Qty (MOQ):	10
NSN:	5310-01-131-4715
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS9276-08 Specifications

Hole Diameter:	0.170 Inches Minimum And 0.175 Inches Maximum
Outside Diameter:	0.310 Inches Minimum And 0.320 Inches Maximum
External Prebent Key Length:	0.080 Inches Minimum And 0.090 Inches Maximum
External Tapered Key Width:	0.175 Inches Minimum And 0.185 Inches Maximum
External Prebent Key Width:	0.080 Inches Minimum And 0.085 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.181 Inches Minimum And 0.191 Inches Maximum
Overall Distance Including Keys:	0.483 Inches Nominal
Split Key Length:	0.115 Inches Nominal
External Key Quantity:	1
Material Thickness:	0.019 Inches Minimum And 0.025 Inches Maximum
Angle Between External Keys:	50.0 Degrees Nominal
External Prebent Key Angle:	15.0 Degrees Nominal
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.