

Description

inner diameter: 3/16, corrosion resistant steel, MS9276 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS927609
Minimum Qty (MOQ):	50
NSN:	5310-00-984-6757
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N MS9276-09 Specifications

Hole Diameter:	0.195 Inches Minimum And 0.200 Inches Maximum
Outside Diameter:	0.370 Inches Minimum And 0.380 Inches Maximum
External Prebent Key Length:	0.095 Inches Minimum And 0.105 Inches Maximum
External Tapered Key Width:	0.200 Inches Minimum And 0.210 Inches Maximum
External Prebent Key Width:	0.110 Inches Minimum And 0.115 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.221 Inches Minimum And 0.231 Inches Maximum
Overall Distance Including Keys:	0.530 Inches Minimum And 0.561 Inches Maximum
Split Key Length:	0.105 Inches Nominal
External Key Quantity:	3
Material Thickness:	0.019 Inches Minimum And 0.025 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
Special Features:	Both Angular Keys Bent 15 Deg In Opposite Direction Of Pre-bent Key
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5576 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.