

## Description

inner diameter: 3/16, corrosion resistant steel, MS9276 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS927609
Minimum Qty (MOQ):	50
NSN:	5310-00-984-6757
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS9276-09 Specifications

<b>Hole Diameter:</b>	0.195 Inches Minimum And 0.200 Inches Maximum
<b>Outside Diameter:</b>	0.370 Inches Minimum And 0.380 Inches Maximum
<b>External Prebent Key Length:</b>	0.095 Inches Minimum And 0.105 Inches Maximum
<b>External Tapered Key Width:</b>	0.200 Inches Minimum And 0.210 Inches Maximum
<b>External Prebent Key Width:</b>	0.110 Inches Minimum And 0.115 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.221 Inches Minimum And 0.231 Inches Maximum
<b>Overall Distance Including Keys:</b>	0.530 Inches Minimum And 0.561 Inches Maximum
<b>Split Key Length:</b>	0.105 Inches Nominal
<b>External Key Quantity:</b>	3
<b>Material Thickness:</b>	0.019 Inches Minimum And 0.025 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>Special Features:</b>	Both Angular Keys Bent 15 Deg In Opposite Direction Of Pre-bent Key
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams 5576 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.