

Description

inner diameter: 3/16, corrosion resistant steel, MS9276 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS927609 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-984-6757 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



P/N MS9276-09 Specifications

| | |
|---|---|
| Hole Diameter: | 0.195 Inches Minimum And 0.200 Inches Maximum |
| Outside Diameter: | 0.370 Inches Minimum And 0.380 Inches Maximum |
| External Prebent Key Length: | 0.095 Inches Minimum And 0.105 Inches Maximum |
| External Tapered Key Width: | 0.200 Inches Minimum And 0.210 Inches Maximum |
| External Prebent Key Width: | 0.110 Inches Minimum And 0.115 Inches Maximum |
| Distance From Centerline To Inside Of Prebent Key: | 0.221 Inches Minimum And 0.231 Inches Maximum |
| Overall Distance Including Keys: | 0.530 Inches Minimum And 0.561 Inches Maximum |
| Split Key Length: | 0.105 Inches Nominal |
| External Key Quantity: | 3 |
| Material Thickness: | 0.019 Inches Minimum And 0.025 Inches Maximum |
| Angle Between External Keys: | 58.0 Degrees Minimum And 62.0 Degrees Maximum |
| Special Features: | Both Angular Keys Bent 15 Deg In Opposite Direction Of Pre-bent Key |
| Material: | Steel Comp 321 Overall |
| Material Document And Classification: | Ams 5576 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Style Designator: | Key |

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.