

Description

diameter: 5/16, keyed, corrosion resistant steel, MS9276 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS927611
Minimum Qty (MOQ):	25
NSN:	5310-00-835-2041
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS9276-11 Specifications

Hole Diameter:	0.320 Inches Minimum And 0.325 Inches Maximum
Outside Diameter:	0.495 Inches Minimum And 0.505 Inches Maximum
External Prebent Key Length:	0.100 Inches Minimum And 0.110 Inches Maximum
External Tapered Key Width:	0.280 Inches Minimum And 0.290 Inches Maximum
External Prebent Key Width:	0.140 Inches Minimum And 0.145 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.325 Inches Minimum And 0.335 Inches Maximum
Overall Distance Including Keys:	0.763 Inches Minimum And 0.791 Inches Maximum
Split Key Length:	0.160 Inches Nominal
External Key Quantity:	3
Material Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
Special Features:	Both Angular Keys Bent 15 Deg In Opposite Direction Of Prebent Key
Material:	Steel Comp 321 Overall
Surface Treatment Document And Classification:	Ams 5510 Assn Std Single Treatment Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.