

Description

Hole Diameter: 3/8", MS9276 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS927612
Minimum Qty (MOQ):	10
NSN:	5310-00-104-5143
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS9276-12 Specifications

Hole Diameter:	0.390 Inches Minimum And 0.395 Inches Maximum
Outside Diameter:	0.560 Inches Minimum And 0.570 Inches Maximum
External Prebent Key Length:	0.140 Inches Minimum And 0.150 Inches Maximum
External Tapered Key Width:	0.320 Inches Minimum And 0.330 Inches Maximum
External Prebent Key Width:	0.140 Inches Minimum And 0.145 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.375 Inches Maximum
Overall Distance Including Keys:	0.856 Inches Nominal
Split Key Length:	0.170 Inches Minimum And 0.175 Inches Maximum
External Key Quantity:	3
Material Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
External Prebent Key Angle:	15.0 Degrees Nominal
Special Features:	Both Angular Keys Bent 15.0 Deg In Opposite Direction Of Prebent Key
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams5510 Assn Std Single Material Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.