

**Description**

Hole Diameter: 3/8", MS9276 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS927612
Minimum Qty (MOQ):	10
NSN:	5310-00-104-5143
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS9276-12 Specifications

<b>Hole Diameter:</b>	0.390 Inches Minimum And 0.395 Inches Maximum
<b>Outside Diameter:</b>	0.560 Inches Minimum And 0.570 Inches Maximum
<b>External Prebent Key Length:</b>	0.140 Inches Minimum And 0.150 Inches Maximum
<b>External Tapered Key Width:</b>	0.320 Inches Minimum And 0.330 Inches Maximum
<b>External Prebent Key Width:</b>	0.140 Inches Minimum And 0.145 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.375 Inches Maximum
<b>Overall Distance Including Keys:</b>	0.856 Inches Nominal
<b>Split Key Length:</b>	0.170 Inches Minimum And 0.175 Inches Maximum
<b>External Key Quantity:</b>	3
<b>Material Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>External Prebent Key Angle:</b>	15.0 Degrees Nominal
<b>Special Features:</b>	Both Angular Keys Bent 15.0 Deg In Opposite Direction Of Prebent Key
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.