

**Description**

Inner diameter: 7/16", corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS927613
Minimum Qty (MOQ):	10
NSN:	5310-00-899-2181
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS9276-13 Specifications

<b>Hole Diameter:</b>	0.450 Inches Minimum And 0.455 Inches Maximum
<b>Outside Diameter:</b>	0.685 Inches Minimum And 0.695 Inches Maximum
<b>External Prebent Key Length:</b>	0.150 Inches Minimum And 0.160 Inches Maximum
<b>External Tapered Key Width:</b>	0.390 Inches Minimum And 0.400 Inches Maximum
<b>External Prebent Key Width:</b>	0.170 Inches Minimum And 0.175 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.415 Inches Minimum And 0.425 Inches Maximum
<b>Overall Distance Including Keys:</b>	0.977 Inches Minimum And 1.000 Inches Maximum
<b>Split Key Length:</b>	0.180 Inches Nominal
<b>External Key Quantity:</b>	3
<b>Material Thickness:</b>	0.032 Inches Minimum And 0.040 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>Special Features:</b>	Both Angular Keys Bent 15 Deg In Opposite Direction Of Prebent Key
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.