

Description

Inner diameter: 7/16", corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS927613 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-899-2181 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS9276-13 Specifications

| | |
|---|--|
| Hole Diameter: | 0.450 Inches Minimum And 0.455 Inches Maximum |
| Outside Diameter: | 0.685 Inches Minimum And 0.695 Inches Maximum |
| External Prebent Key Length: | 0.150 Inches Minimum And 0.160 Inches Maximum |
| External Tapered Key Width: | 0.390 Inches Minimum And 0.400 Inches Maximum |
| External Prebent Key Width: | 0.170 Inches Minimum And 0.175 Inches Maximum |
| Distance From Centerline To Inside Of Prebent Key: | 0.415 Inches Minimum And 0.425 Inches Maximum |
| Overall Distance Including Keys: | 0.977 Inches Minimum And 1.000 Inches Maximum |
| Split Key Length: | 0.180 Inches Nominal |
| External Key Quantity: | 3 |
| Material Thickness: | 0.032 Inches Minimum And 0.040 Inches Maximum |
| Angle Between External Keys: | 58.0 Degrees Minimum And 62.0 Degrees Maximum |
| Special Features: | Both Angular Keys Bent 15 Deg In Opposite Direction Of Prebent Key |
| Material: | Steel Comp 321 Overall |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Overall |
| Style Designator: | Key |

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.